

Based on the 2010 ADA Standards for Accessible Design



Produced by

Institute for Human Centered Design www.HumanCenteredDesign.org

www.ADAchecklist.org Copyright © 2016



ADA National Network www.ADAta.org

Questions on the ADA 800-949-4232 voice/tty Questions on checklist 617-695-0085 voice/tty ADAinfo@NewEnglandADA.org

This checklist was produced by the New England ADA Center, a project of the Institute for Human Centered Design and a member of the ADA National Network. This checklist was developed under a grant from the Department of Education, NIDRR grant number H133A060092-09A. However the contents do not necessarily represent the policy of the Department of Education, and you should not assume endorsement by the Federal Government.

Questions or comments on the checklist contact the New England ADA Center at 617-695-0085 voice/tty or ADAinfo@NewEnglandADA.org

For the full set of checklists, including the checklists for recreation facilities visit www.ADAchecklist.org.

Copyright © 2016 ADA Checklist for Existing Materials. You can freely reproduce and distribute this content. Include proper attribution. But you must get permission before using this content as a fee-based product.

ADA Checklist for Existing Facilities

The Americans with Disabilities Act (ADA) requires state and local governments, businesses and non-profit organizations to provide goods, services and programs to people with disabilities on an equal basis with the rest of the public.

Some people think that only new construction and alterations need to be accessible and that older facilities are "grandfathered," but that's not true. Because the ADA is a civil rights law and not a building code, older facilities are often required to be accessible to ensure that people with disabilities have an equal opportunity to participate.

The ADA has different requirements for state and local governments and for places of public accommodation (businesses and non-profit organizations that serve the public).

Requirements for State and Local Governments

State and local governments must ensure that services, programs and activities, when viewed in their entirety, are accessible to people with disabilities. This is part of public entities' program accessibility obligations. Alterations to older buildings may be needed to ensure program accessibility. Generally this is a greater obligation than "readily achievable barrier removal" the standard that applies to public accommodations. State and local governments are not required to take any action that would result in undue financial and administrative burdens.

State and local governments' ADA obligations for program accessibility are in the Department of Justice's ADA Title II regulations 28 CFR Part 35.150.

How to Use this Checklist

Get Organized

One person can conduct a survey, but it's easier with two people. One person can take measurements and the other person can fill out the checklist and take photos.

Obtain Floor Plan or Make Sketch

A floor plan helps the surveyors to get organized and to know how many elements there are, such as entrances and toilet rooms. If plans are not available, sketch the exterior and interior layout of interior and exterior spaces and mark the elements on the sketch.

Make Copies of the Checklist

Determine how many copies of each section of the checklist you need. For example, most facilities have more than one toilet room.

Gather Tools

- Checklist
- Clipboard
- Tape measure
- Electronic or carpenter's level 24 inches
- Door pressure gauge or fish scale
- Camera
- Bag to hold these items

Requirements for Places of Public Accommodation

Businesses and non-profit organizations that serve the public must remove architectural barriers when it is "readily achievable" to do so; in other words, when barrier removal is "easily accomplishable and able to be carried out without much difficulty or expense."

The decision of what is readily achievable is made considering the size, type, and overall finances of the public accommodation and the nature and cost of the access improvements needed. Barrier removal that is difficult now may be readily achievable in the future as finances change.

Public accommodations' ADA obligations for barrier removal are in the Department of Justice's ADA Title III regulations 28 CFR Part 36.304.

Priorities for Accessibility

The checklist follows the four priorities that are listed in the Department of Justice ADA Title III regulations. These priorities are equally applicable to state and local government facilities.

Priority 1 - Accessible approach and entrance

Priority 2 - Access to goods and services

Priority 3 - Access to public toilet rooms

Priority 4 - Access to other items such as water fountains and public telephones

Conduct the Survey

Start Outside

Start from site arrival points such as drop-off areas and sidewalks. Determine if there is an accessible route to an accessible entrance. If there is a parking lot or garage check for the correct number of accessible parking spaces, including van-accessible spaces. Is there an accessible route from the accessible parking spaces to an accessible entrance? Next survey the entrances. If there is an accessible entrance, determine if there are signs at inaccessible entrances directing people to the accessible entrance. Go inside and continue through the facility.

Keep Good Notes

Write on the front of each checklist where you are surveying. You may end up with six toilet room checklists. When you get back to your office you'll want to know which one is the checklist for the first floor women's room. If there isn't an accessible entrance you'll want to indicate how many steps there are and how much space is available to install a ramp or lift. This is a good time to take photographs.

Take Good Measurements

When in doubt write it down. It's better to have too much information than not enough. Even if something is in compliance it's helpful to have exact measurements.

2010 ADA Standards for Accessible Design

The checklist is based on the 2010 ADA Standards for Accessible Design (2010 Standards). The checklist does not include all sections of the 2010 Standards. For example there are no questions about patient rooms in hospitals or guest rooms in hotels. Consult the 2010 Standards for situations not covered in the checklist. Full compliance with the 2010 Standards is required only for new construction and alterations.

Safe Harbor – Construction Prior to March 15, 2012

Elements in facilities built or altered before March 15, 2012 that comply with the 1991 ADA Standards for Accessible Design (1991 Standards) are not required to be modified to specifications in the 2010 Standards. For example, the 1991 Standards allow 54 inches maximum for a side reach range to a control such as the operating part of a paper towel dispenser. The 2010 Standards lower that side reach range to 48 inches maximum. If a paper towel dispenser was installed prior to March 15, 2012 with the highest operating part at 54 inches, the paper towel dispenser does not need to be lowered to 48 inches.

Elements in the 2010 Standards that aren't in the 1991 Standards

The 2010 Standards contain elements that are not in the 1991 Standards. These elements include recreation facilities such as swimming pools, team and player seating, accessible routes to court sports facilities, saunas and steam rooms, fishing piers, play areas, exercise machines, golf facilities, miniature golf facilities, amusement rides, shooting facilities with firing positions, and recreational boating facilities. Because these elements are not in the 1991 Standards, they are not subject to the safe harbor exemption. State and local governments must make these items



Parking Spaces

Measure from the center of marking lines. If lines are not adjacent to another space or aisle the measurement can be to the full width of the line.




Door Clear Width

Open the door 90 degrees, measure from the face of the door to the edge of the door stop.



Door Opening Force

If you're using a door pressure gauge place it where you would push open the door.



If you're using a fish scale place it where you would pull open the door.

accessible if necessary to ensure program accessibility, unless an undue burden would result. Public accommodations must remove architectural barriers to these items.

What this Checklist is Not

The ADA Title II and III regulations require more than program accessibility and barrier removal. The regulations include requirements for nondiscriminatory policies and practices and for the provision of auxiliary aids and services, such as sign language interpreters for people who are deaf and material in Braille for people who are blind. This checklist does not cover those requirements.

Since this checklist does not include all of the 2010 Standards it is not intended to determine compliance for new construction or facilities being altered.

What are Public Accommodations?

Under the ADA public accommodations are private entities that own, lease, lease to or operate a place of public accommodation. This means that both a landlord who leases space in a building to a tenant and the tenant who operates a place of public accommodation have responsibilities to remove barriers.

A place of public accommodation is a facility whose operations affect commerce and fall within at least one of the following 12 categories:

- 1) Places of lodging (e.g., inns, hotels, motels, except for owner-occupied establishments renting fewer than six rooms)
- 2) Establishments serving food or drink (e.g., restaurants and bars)
- 3) Places of exhibition or entertainment (e.g., motion picture houses, theaters, concert



Accessible Slopes

You can measure slope with a 24 inch level and a tape measure. Put the level on the surface in the direction you are

measuring. Put one end at the high point of the surface and raise the other end so that the bubble is in the middle of the level's gauge. The level is now level. Measure the distance between the end of the level at its bottom point and the surface.

For a ramp the maximum running slope allowed is 1:12. That means for every inch of height change there should be at least 12 inches of ramp run. If the distance between the bottom of the level and the ramp surface is 2 inches or less, then the slope is 1:12 or less (2:24 = 1:12 and 1.5:24 = 1:16 which is a more gradual slope than 1:12). If the distance is greater than 2 inches, the ramp is too steep. For example, if the distance is 3 inches, then the slope is 1:8 (3:24 = 1:8 which is a steeper slope than 1:12).

For the parts of an accessible route that aren't a ramp, the maximum running slope allowed is 1:20. That means for every inch of height change there must be at least 20 inches of route run. The distance from the bottom edge of the level to the surface should be no more than 1.2 inches (1.2:24 = 1:20).

halls, stadiums)

- 4) Places of public gathering (e.g., auditoriums, convention centers, lecture halls)
- 5) Sales or rental establishments (e.g., bakeries, grocery stores, hardware stores, shopping centers)
- 6) Service establishments (e.g., laundromats, dry-cleaners, banks, barber shops, beauty shops, travel services, shoe repair services, funeral parlors, gas stations, offices of accountants or lawyers, pharmacies, insurance offices, professional offices of health care providers, hospitals)
- 7) Public transportation terminals, depots, or stations (not including facilities relating to air transportation)
- 8) Places of public display or collection (e.g., museums, libraries, galleries)
- 9) Places of recreation (e.g., parks, zoos, amusement parks)
- 10) Places of education (e.g., nursery schools, elementary, secondary, undergraduate, or postgraduate private schools)
- 11) Social service center establishments (e.g., day care centers, senior citizen centers, homeless shelters, food banks, adoption agencies)
- 12) Places of exercise or recreation (e.g., gymnasiums, health spas, bowling alleys, golf courses).

For the cross slope of an accessible route the maximum slope allowed is 1:48. The distance from the bottom edge of the level to the surface should be no more than $\frac{1}{2}$ inch (.5:24 = 1:48). The cross slope of an accessible route is the slope that is perpendicular to the direction of pedestrian travel.

Slopes may also be measured using a digital level. Be sure to read the instructions. Measure with the percent calculation rather than the degrees calculation. For a ramp the maximum running slope allowed is 8.33% (8.33% is a 1:12 slope). For an accessible route without a ramp the maximum running slope allowed is 5% (1:20). For the cross slope of an accessible route the maximum slope allowed is 2.083% (1:48).

Check that You Got Everything - Before you leave the site review all the checklists. Make sure you know which checklist goes with which entrance and which toilet room and that you've got all the information you need. It is better to do it now than to have to go back.

After the Survey

List Barriers and Solutions - Consider the solutions listed beside each question on the checklist and add your own ideas. Consult with building contractors and equipment suppliers to estimate the costs for making modifications.

Resources

U.S. Department of Justice ADA Information

800-514-0301 voice 800-514-0383 TTY www.ada.gov

ADA National Network

800-949-4232 voice/TTY connects to your regional ADA Center www.adata.org

U.S. Access Board

800- 872-2253 voice 800-993-2822 TTY www.access-board.gov

ADA Title III Regulations 28 CFR Part 36

www.ada.gov/regs2010/titleIII_2010/titleIII_2010_regulations.htm

2010 ADA Standards for Accessible Design

www.ada.gov/2010ADAstandards index.htm

1991 ADA Standards for Accessible Design

www.ada.gov/stdspdf.htm

Tax Deductions and Credits for Barrier Removal

www.ada.gov/taxincent.htm

Acknowledgements

Many of the illustrations are from the U.S. Department of Justice and the U.S. Access Board or are based on illustrations produced by the U.S. Access Board and the U.S. Department of Justice.

Develop an Implementation Plan -

Although an implementation plan is not required, the Department of Justice recommends such a plan, specifying what barriers will be removed and when solutions will occur: "...Such a plan...could serve as evidence of a good faith effort to comply..." Prioritize items, make a timeline and develop a budget. Where the removal of barriers is not readily achievable, consider whether there are alternative methods for providing access that are readily achievable such as curbside takeout service at a restaurant with an accessible intercom system outside.


Make Changes - Use the 2010 ADA Standards for Accessible Design. Note: Until March 15, 2012 the 1991 ADA Standards for Accessible Design may be used for readily achievable barrier removal. Check whether local and state building codes require greater accessibility when alterations are undertaken.

Follow Up - Review the implementation plan each year to evaluate whether more access improvements have become readily achievable.

ADA Checklist for Existing Facilities

Priority 1 – Approach & Entrance

Based on the 2010 ADA Standards for Accessible Design



Project

Building West Annex

Location West side of building - Coroner's Office

Date 10/11/2021

Surveyors Larry Weaver

Sheri Gaillard

Contact Information

574-242-2508

An accessible route from site arrival points and an accessible entrance should be provided for everyone.



Institute for Human Centered Design www.HumanCenteredDesign.org 2014



ADA National Network
Questions on the ADA 800-949-4232 voice/tty
www.ADAchecklist.org

This checklist was produced by the New England ADA Center, a project of the Institute for Human Centered Design and a member of the ADA National Network. This checklist was developed under a grant from the Department of Education, NIDRR grant number H133A060092-09A. However the contents do not necessarily represent the policy of the Department of Education, and you should not assume endorsement by the Federal Government.

Questions or comments on the checklist contact the New England ADA Center at 617-695-0085 voice/tty or ADAinfo@NewEnglandADA.org

For the full set of checklists, including the checklists for recreation facilities visit www.ADAchecklist.org.

Copyright © 2016 ADA Checklist for Existing Materials. You can freely reproduce and distribute this content. Include proper attribution. But you must get permission before using this content as a fee-based product.

Prio	rity 1 – Approach & Entra	ince				Comments	Possible Solutions
1.1	Is there at least one route from site arrival points (parking, passenger loading zones, public sidewalks and public transportation stops) that does not require the use of stairs? [See 2010 ADA Standards for Accessible Design – 206.2.1]	Yes If yes, loca of route:Si story build	ngle			Photo #:	 Add a ramp Regrade to 1:20 maximum slope Add a lift if site constraints prevent other solutions
Park	ing Accessible parking spaces should b	e identified b	y size, a	access aisle and signa	ge.	<u> </u>	
1.2	If parking is provided for the public, are an adequate number	⊠Yes [No	Total Spaces	Accessible Spaces		Reconfigure by repainting lines
	of accessible spaces provided?	Total #:24		1 - 25	1		•
	[208.2]	Accessible	#:	26 - 50	2		•
		1		51 - 75	3		
				76 - 100	4		
				100+ see 2010 St	andards 208.2	Photo #:	
1.3	Of the accessible spaces, is at least one a van accessible space?* [208.2.4]	XYes [No	*For every 6 or fra spaces required by at least 1 should b space.	the table above,		* If constructed before 3/15/2012, parking is compliant if at least 1 in every 8 accessible spaces is van accessible
						Photo #:	Reconfigure by repainting lines

1.4	Are accessible spaces at least 8 feet wide with an access aisle at least 5 feet wide? [502.2, 502.3] Note: Two spaces may share an access aisle. Check state/local requirements; some specify that each space have its own aisle.	Yes No Measurement: 8x5	8'min → 5'min →	Photo #:	 Reconfigure by repainting lines •
1.5	Is the van accessible space: At least 11 feet wide with an access aisle at least 5 feet wide? Or At least 8 feet wide with an access aisle at least 8 feet wide? Is the van accessible space:	Yes No Measurement: 11x5 Yes No Measurement:	or $-11'\min$ $-8'\min$ $-8'\min$ $-8'\min$	Photo #:	 Reconfigure to provide van-accessible space(s) •
1.6	Is at least 98 inches of vertical clearance provided for the van accessible space? [502.5]	Yes No Measurement: Open Air	98"min	Photo #:	 Reconfigure to provide van-accessible space(s) •

1.7	Are the access aisles marked so as to discourage parking in them? [502.3.3] Note: The marking method and color may be addressed by state/local requirements.	Yes No	area to be marked	Photo #:	Mark access aisles
1.8	Is the slope of the accessible parking spaces and access aisles no steeper than 1:48 in all directions? [502.4]	Yes No Measurement: 1.5:48		Photo #:	 Regrade surface Pave parking lot. It is currently gravel and vans are to open to the sidewalk which is non-compliant in this area
1.9	Do the access aisles adjoin an accessible route? [502.3]	Yes No		Photo #:	 Create accessible route Relocate accessible space
1.10	Are accessible spaces identified with a sign that includes the International Symbol of Accessibility? Is the bottom of the sign at least 60 inches above the ground? [502.6] Note: The International Symbol of Accessibility is not required on the ground.	Yes No Yes No Measurement: 41.5"	60"min	Photo #:	• Install signs •

1.11	Are there signs reading "van accessible" at van accessible spaces? [502.6]	Yes No	SAN ACCESSIBLE	Photo #:	Install signs
1.12	Of the total parking spaces, are the accessible spaces located on the closest accessible route to the accessible entrance(s)? [208.3.1] Note: If parking serves multiple entrances, accessible parking should be dispersed.	Yes No		Photo #:	 Reconfigure spaces •
Exter	ior Accessible Route				
1.13	Is the route stable, firm and slip-resistant? [302.1]	Yes No		Photo #:	 Repair uneven paving Fill small bumps and breaks with patches Replace gravel with asphalt or other surface
1.14	Is the route at least 36 inches wide? [403.5.1]	Yes No Measurement: 60"	36"min		Change or move landscaping, furnishings or other items Widen route

	Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.		32"min 32"min	Photo #:	
1.15	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: 60"	36"min 60"min	Photo #:	Widen route for passing space
1.16	If there are grates or openings on the route, are the openings no larger than ½ inches? Is the long dimension perpendicular to the dominant direction of travel? [302.3]	Yes No Measurement: Yes No	1/2" max	NA Photo #:	 Replace or move grate •
1.17	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement: .25:20		Photo #:	• Regrade to 1:20 max. •

Institute for Human Centered Design Copyright © 2016

www.ADAchecklist.org

1.18	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		NA Photo #:	• Regrade to 1:48 max. •
Curb	Ramps				
1.19	If the accessible route crosses a curb, is there a curb ramp? [402.2]	Yes No		NA Photo #:	 Install curb ramp •
1.20	Is the running slope of the curb ramp no steeper than 1:12, i.e. for every inch of height change there are at least 12 inches of curb ramp run? [406.1, 405.2]	Yes No Measurement:	1 12 min 1	NA Photo #:	Regrade curb ramp
1.21	Is the cross slope of the curb ramp, excluding flares, no steeper than 1:48? [406.1, 405.3]	Yes No Measurement:	48 min 1	NA Photo #:	Regrade curb ramp

1.22	Is the curb ramp, excluding flares, at least 36 inches wide? [406.1, 405.5]	Yes No Measurement:	36"min	NA Photo #:	• Widen curb ramp •
1.23	At the top of the curb ramp is there a level landing (slope no steeper than 1:48 in all directions) that is at least 36 inches long and at least as wide as the curb ramp? [406.4] If there are curb ramp flares, are the slopes of the flares no steeper than 1:10, i.e. for every inch of height change there are at least 10 inches of flare run? [406.3]	Yes No Measurement: Yes No Measurement:	36"min	NA Photo #:	Reconfigure Add ramp flares
1.24	If the landing at the top is less than 36 inches long, are there curb ramp flares? Are the slopes of the flares no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of flare run? [406.4]	Yes No Yes No Measurement:	12 min 1	NA Photo #:	Add ramp flares Regrade flares

Ramp	Ramps If any portion of the accessible route is steeper than 1:20, it should be treated as a ramp.					
1.25	If there is a ramp is it at least 36 inches wide? [405.5] Note: If there are handrails, measure between the handrails.	Yes No Measurement: 48"	36"min	Photo #:	Alter ramp	
1.26	Is the surface stable, firm and slip resistant? [405.4]	Yes No		Photo #:	Resurface ramp	
1.27	For each section of the ramp, is the running slope no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of ramp run? [405.2] Note: Rises no greater than 3 inches with a slope no steeper than 1:8 and rises no greater than 6 inches with a slope no steeper than 1:10 are permitted when such slopes are necessary due to space limitations.	.5.12	12 min	Photo #:	Relocate ramp Lengthen ramp to decrease slope	

1.28	Is there a level landing that is at least 60 inches long and at least as wide as the ramp:				Alter ramp Relocate ramp
	At the top of the ramp?	Yes No	landing widths must be at least equal to		
	At the bottom of the ramp? [405.7.2, 405.7.3]	Measurement: Yes No Measurement:	ramp width	Photo #:	
1.29	Is there a level landing where the ramp changes direction that is at least 60 x 60 inches? [405.7.4]	Yes No Measurement:	60 min	Photo #:	 Alter ramp Increase landing size
1.30	If the ramp has a rise higher than 6 inches, are there handrails on both sides? [405.8] Note: Curb ramps are not required to have handrails.	Yes No Measurement:	if greater than 6"	NA Photo #:	Add handrails

1.31	Is the top of the handrail gripping surface no less than 34 inches and no greater than 38 inches above the ramp surface? [505.4]	Yes No Measurement:	34"-38"	NA	 Reconfigure or replace handrails Adjust handrail height
1.32	Is the handrail gripping surface continuous and not obstructed along the top or sides? [505.3] If there are obstructions, is the bottom of the gripping surface obstructed no greater than 20%? [505.6]	Yes No Yes No Measurement:		Photo #: NA Photo #:	Reconfigure or replace handrails
1.33	If the handrail gripping surface is circular, is it no less than 1 ¼ inches and no greater than 2 inches in diameter? [505.7.1]	Yes No Measurement:	11/4-2*	NA Photo #:	• Replace handrails •
1.34	If the handrail gripping surface is non-circular: Is the perimeter no less than 4 inches and no greater than 6¼ inches?	Yes No Measurement:	4"-6 1/4" perimeter	NA	Replace handrails

	Is the cross section no greater than 2¼ inches? [505.7.2]	Yes No Measurement:		Photo #:	
1.35	Does the handrail: Extend at least 12 inches horizontally beyond the top and bottom of the ramp? Return to a wall, guard, or landing surface? [505.10.1] Note: If a 12 inch extension would be a hazard (in	Yes No Measurement: Yes No	min min	NA	• Alter handrails •
	circulation path) it is not required.			Photo #:	
1.36	To prevent wheelchair casters and crutch tips from falling off: Does the surface of the ramp extend at least 12 inches beyond the inside face of the handrail? Or Is there a curb or barrier that prevents the passage of a 4-inch diameter sphere? [405.9.1, 405.9.2]	Yes No Measurement: Yes No Measurement:	12"min	NA Photo #:	 Add curb Add barrier Extend ramp width
	[405.9.1, 405.9.2]			Photo #:	

Entra	Entrance						
1.37	Is the main entrance accessible?	Xes No		Photo #:	Redesign to make it accessible•		
1.38	If the main entrance is not accessible, is there an alternative accessible entrance? Can the alternative accessible entrance be used independently and during the same hours as the main entrance?	Yes No		NA Photo #:	 Designate an entrance and make it accessible Ensure that accessible entrance can be used independently and during the same hours as the main entrance 		
1.39	Do all inaccessible entrances have signs indicating the location of the nearest accessible entrance? [216.6]	Yes No	ACCESSIBLE ENTRANCE	NA Photo #:	 Install signs Install signs on route before people get to inaccessible entrances so that people do not have to turn around and retrace route 		
1.40	If not all entrances are accessible, is there a sign at the accessible entrance with the International Symbol of Accessibility? [216.6]	Yes No	E	NA Photo #:	• Install sign •		

1.41	Is the clear opening width of the accessible entrance door at least 32 inches, between the face of the door and the stop, when the door is open 90 degrees? [404.2.3]	Yes No Measurement: 32"	32" min————————————————————————————————————	Photo #:	 Alter door Install offset hinges
1.42	If there is a front approach to the pull side of the door, is there at least 18 inches of maneuvering clearance beyond the latch side plus at least 60 inches clear depth? Note: See 2010 Standards 404.2.4 for maneuvering clearance requirements on the push side of the door and side approaches to the pull side of the door On both sides of the door, is the ground or floor surface of the maneuvering clearance level (no steeper than 1:48)? [404.2.4]	Yes No Measurement: 32" Yes No Measurement:	60" min	Photo #:	Remove obstructions Reconfigure walls Add automatic door opener Page 14
1.43	If the threshold is vertical is it no more than ¼ inch high? Or No more than ½ inch high with the top ¼ inch beveled no steeper than 1:2, if the threshold was installed on or	Yes No Measurement: 3/8" Yes No Measurement:	1/4"max-+::-		Remove or replace threshold

	after the 1991 ADA Standards went into effect (1/26/93)? Or No more than ¾ inch high with the top ½ inch beveled no steeper than 1:2, if the threshold was installed before	Yes No Measurement:	1/2"max -[
	the 1991 ADA Standards went into effect (1/26/93)? [404.2.5, 303.2]				
	Note: The first ¼ inch of the ½ or ¾ inch threshold may be vertical; the rest must be beveled.		3/4"max +[Photo #:	
1.44	Is the door equipped with hardware that is operable with one hand and does not require tight grasping, pinching or twisting of the wrist?	Yes No			 Replace inaccessible knob with lever, loop or push hardware Add automatic door opener
	Door handle?	Yes No			
	Lock (if provided)? [404.2.7]	Yes No		Photo #:	


1.45	Are the operable parts of the door hardware no less than 34 inches and no greater than 48 inches above the floor or ground surface? [404.2.7]	Yes No Measurement: 37.5"	34"-48"	Photo #:	 Change hardware height •
1.46	If the door has a closer, does it take at least 5 seconds to close from an open position of 90 degrees to a position of 12 degrees from the latch? [404.2.8]	Yes No Measurement:	90° 12°	NA Photo #:	• Adjust closer •
1.47	If there are two doors in a series, e.g. vestibule, is the distance between the doors at least 48 inches plus the width of the doors when swinging into the space? [404.2.6]	Yes No Measurement:	or 48"min or	NA	Remove inner door Change door swing

			48"min —	Photo #:	
1.48	If provided at the building entrance, are carpets or mats no higher than ½ inch thick? [302.2]	Yes No Measurement:	½"max	Photo #:	Replace or remove mats
1.49	Are edges of carpets or mats securely attached to minimize tripping hazards? [302.2]	Yes No		Photo #:	Secure carpeting or mats at edges
		Yes No		Photo #:	•
		Yes No		Photo #:	•

ADA Checklist for Existing Facilities

Priority 2 – Access to Goods & Services

Based on the 2010 ADA Standards for Accessible Design



The layout of the building should allow people with disabilities to obtain goods and services and to participate in activities without assistance.





This checklist was produced by the New England ADA Center, a project of the Institute for Human Centered Design and a member of the ADA National Network. This checklist was developed under a grant from the Department of Education, NIDRR grant number H133A060092-09A. However the contents do not necessarily represent the policy of the Department of Education, and you should not assume endorsement by the Federal Government.

Questions or comments on the checklist contact the New England ADA Center at 617-695-0085 voice/tty or ADAinfo@NewEnglandADA.org

For the full set of checklists, including the checklists for recreation facilities visit www.ADAchecklist.org.

Copyright © 2016 ADA Checklist for Existing Materials. You can freely reproduce and distribute this content. Include proper attribution. But you must get permission before using this content as a fee-based product.

Prio	rity 2 – Access to Goods 8	& Services		Comments	Possible Solutions
2.1	Does the accessible entrance provide direct access to the main floor, lobby and elevator? [See 2010 ADA Standards for	Yes No			• Create accessible route •
	Accessible Design – 206.4]			Photo #:	
Inter	ior Accessible Route				
2.2	Are all public spaces on at least one accessible route? [206.2.4]	Yes No			• Create accessible route •
				Photo #:	
2.3	Is the route stable, firm and slip-resistant? [40.2, 302.1]	Yes No			Repair uneven surfaces
				Photo #:	
2.4	Is the route at least 36 inches wide? [403.5.1] Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.	Yes No Measurement: 36'	36"min		• Widen route •

			424"max + 48"min — 24"max + 32"min	Photo #:	
2.5	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement: 64"	36"min 60"min	Photo #:	Widen route for passing space
2.6	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3] Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No Measurement:		NA Photo #:	• Regrade •
2.7	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		NA Photo #:	• Regrade •

Priority 2 – Access to Goods & Services

2.8	Do all objects on circulation paths through public areas, e.g. fire extinguishers, drinking fountains, signs, etc., protrude no more than 4 inches into the path? Or If an object protrudes more than 4 inches, is the bottom leading edge at 27 inches or lower above the floor? [307.2] Or Is the bottom leading edge at 80 inches or higher above the floor? [307.4]	Yes No Measurement: Yes No Measurement: Yes No Measurement:	Or BATHROOM BATHROOM 80"min	Photo #:	 Remove object Add tactile warning such as permanent planter or partial walls
2.9	Are there elevators or platform lifts to all public stories? Note: Vertical access is not required in new construction or alterations if a facility is less than three stories or has less than 3,000 square feet per story, unless the facility is a shopping center, shopping mall,	Yes No		NA	Install if necessary Offer goods and services on an accessible story

professional office of a health			
care provider, transportation			
terminal, state facility or local			
government facility		Photo #:	

Ramp	os				
2.10	If there is a ramp, is it at least 36 inches wide? [405.5] Note: If there are handrails, measure between the handrails.	Yes No Measurement:	36"min	NA	Alter ramp•
				Photo #:	
2.11	Is the surface stable, firm and slip resistant? [405.4]	Yes No			Resurface ramp
				Photo #:	
2.12	For each section of the ramp, is the running slope no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of ramp run? [405.2] Note: Rises no greater than 3	Yes No Measurement:	1 12 min	NA	Lengthen ramp to decrease slope Relocate ramp
	inches with a slope no steeper than 1:8 and rises no greater than 6 inches with a slope no steeper than 1:10 are				

Institute for Human Centered Design Copyright © 2016

www.ADAchecklist.org

Priority 2 – Access to Goods & Services

	permitted when due to space limitations.			Photo #:	
2.13	Is there a level landing that is at least 60 inches long and at least as wide as the ramp:				Alter ramp Relocate ramp
	At the top of the ramp?	Yes No Measurement:	landing widths must be at least equal to ramp width		
	At the bottom of the ramp? [405.7.2, 405.7.3]	Yes No Measurement:	*60"min*		
				Photo #:	
2.14	Is there a level landing where the ramp changes direction that is at least 60 x 60 inches? [405.7.4]	Yes No Measurement:	60°min	NA	 Increase landing size •
				Photo #:	

Priority 2 – Access to Goods & Services

2.15	If the ramp has a rise higher than 6 inches are there handrails on both sides? [405.8]	Yes No Measurement:	if greater than 6"	NA Photo #:	Add handrails
2.16	Is the top of the handrail gripping surface no less than 34 inches and no greater than 38 inches above the ramp surface? [505.4]	Yes No Measurement:	34".38"	NA Photo #:	 Adjust handrail height •
2.17	Is the handrail gripping surface continuous and not obstructed along the top or sides? [505.3] If there are obstructions, is the bottom of the gripping surface obstructed no more than 20%? [505.6]	Yes No Yes No Measurement:		NA Photo #:	Reconfigure or replace handrails
2.18	If the handrail gripping surface is circular, is it no less than 1 ¼ inches and no greater than 2 inches in diameter? [505.7.1]	Yes No Measurement:	11/4-214	NA Photo #:	Replace handrails

2.19	If the handrail gripping surface is non-circular:			NA	Replace handrails
	Is the perimeter no less than 4 inches and no greater than 6¼ inches?	Yes No Measurement:	21/2		•
	Is the cross section no greater than 2¼ inches in diameter? [505.7.2]	Yes No Measurement:	4"-6 1/4" perimeter	Photo #:	
2.20	Does the handrail:			NA	Alter handrails
	Extend at least 12 inches horizontally beyond the top and bottom of the ramp? Return to a wall, guard, or landing surface?	Yes No Measurement: Yes No	12"		•
	[505.10.1]		min		
	Note: If a 12" extension would be hazardous (in circulation path), it is not required.		min	Photo #:	
2.21	To prevent wheelchair casters and crutch tips from falling off:			NA	Add curb Add barrier
	Does the surface of the ramp extend at least 12 inches beyond the inside face of the handrail? Or Is there a curb or barrier that prevents the passage of a 4-inch diameter sphere?	Yes No Measurement: Yes No Measurement:	12"min less than 4"		Extend ramp width
	[405.9.1, 405.9.2]			Photo #:	

Elevators – Full Size & LULA (limited use, limited application) LULA elevators are often used in alterations.					
2.22	If there is a full size or LULA elevator, are the call buttons no higher than 54 inches above the floor? [407.2.1.1]	Yes No Measurement:	54"max	NA Photo #:	 Change call button height
2.23	If there is a full size or LULA elevator, does the sliding door reopen automatically when obstructed by an object or person?* [407.3.3]	Yes No		NA Photo #:	* If constructed before 3/15/2012 and manually operated, the door is not required to reopen automatically • Install opener •
2.24	If there is a LULA elevator with a swinging door: Is the door power- operated? Does the door remain open for at least 20 seconds when activated? [403.3.2]	Yes No Yes No Time:		NA Photo #:	 Add power operated door Adjust opening time
2.25	If there is a full size elevator: Is the interior at least 54 inches deep by at least 36 inches wide with at least 16 sq. ft. of clear floor area? Is the door opening width at	Yes No Measurement:	4—36"min → 54"min	NA	Replace elevator•

	least 32 inches? [407.4.1 Exception]	Measurement:		Photo #:	
2.26	If there is a LULA elevator, is the interior: At least 51 inches deep by 51 inches wide with a door opening width of at least 36 inches? Or At least 54 inches deep by at least 36 inches wide with at least 15 sq. ft. of clear floor area and a door opening width of at least 32 inches? [408.4.1 Exceptions 1 and 2]	Yes No Measurement: Yes No Measurement:	51"min ——36"min ——36"	NA Photo #:	• Replace elevator •
2.27	If there is a full size or LULA elevator, are the in-car controls: No less than 15 inches and no greater 48 inches above the floor? Or Up to 54 inches above the floor for a parallel approach? [408.4.6, 407.4.6.1]	Yes No Measurement: Yes No Measurement:	48"max 15"min	NA	• Change control height •


			54"max 15"min	Photo #:	
2.28	If there is a LULA elevator, are the in-car controls centered on a side wall? [408.4.6]	Yes No Measurement:		NA Photo #:	 Reconfigure controls •
2.29	If there is a full size or LULA elevator: Are the car control buttons designated with raised characters? Are the car control buttons designated with Braille? [407.4.7.1, 703.2]	Yes No	5 6 0 3 0 4 0 *1 0 2 0	NA Photo #:	 Add raised characters Add Braille
2.30	If there is a full size elevator, are there audible signals which sound as the car passes or is about to stop at a floor? [407.4.8]	Yes No		NA Photo #:	Install audible signals

2.31	If there is a full size or LULA elevator: Is there a sign on both door jambs at every floor identifying the floor? Is there a tactile star on both jambs at the main entry level? Do text characters contrast with their backgrounds? Are text characters raised? Is there Braille? Is the sign mounted between 48 inches to the baseline of the lowest character and 60 inches	Yes No Measurement:	48"min	NA	 Install signs Change sign height * If constructed before 3/15/2012 and mounted
	to the baseline of the highest character above the floor?* [407.2.3, 408.2.3]			Photo #:	no higher than 60 inches to the centerline of the sign, relocation is not required
Platfo	orm Lifts				
2.32	If a lift is provided, can it be used without assistance from others? [410.1]	Yes No		NA Photo #:	 Reconfigure so independently operable •


2.33	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a person using a wheelchair to approach and reach the controls to use the lift? [410.5]	Yes No Measurement:	48"min 30"min 48"min	NA Photo #:	 Remove obstructions •
2.34	Are the lift controls no less than 15 inches and no greater than 48 inches above the floor? [410.5]	Yes No Measurement:	15"-48"	NA Photo #:	 Change control height
2.35	Is there a clear floor space at least 36 inches wide by at least 48 inches long inside the lift? [410.3]	Yes No Measurement:	36 " min48" min	NA Photo #:	• Replace lift •
2.36	If there is an end door, is the clear opening width at least 32 inches? [410.6]	Yes No Measurement:	32"min	NA Photo #:	Alter door width

2.37	If there is a side door, is the clear opening width at least 42	Yes No		NA	Alter door width
	inches? [410.6]	Measurement:	42"min		•
				Photo #:	

Signs	"Tactile characters" are read using to	uch, i.e. raised charac	cters and Braille.		
2.38	If there are signs designating permanent rooms and spaces not likely to change over time, e.g. room numbers and letters, room names, and exit signs: [216.2]			NA	Install tactile signRelocate sign
	Do text characters contrast with their backgrounds? [703.5] Are text characters raised? [703.2]	Yes No	354 LIBRARY		
	Is there Braille? [703.3]	Yes No			
	Is the sign mounted: On the wall on the latch side of the door? [703.4.2]	Yes No			
	Note: Signs are permitted on the push side of doors with				



Note: Raised characters and Braille are not required.		Photo #:	



	the door. On both sides of the door, is the floor surface of the maneuvering clearance level (no steeper than 1:48)? [404.2.4]	Yes No Measurement:		Photo #:	
2.42	If the threshold is vertical is it no more than ¼ inch high? Or No more than ½ inch high with the top ¼ inch beveled no steeper than 1:2, if the threshold was installed on or after the 1991 ADA Standards went into effect (1/26/93)? Or No more than ¾ inch high with the top ½ inch beveled no steeper than 1:2, if the threshold was installed before the 1991 ADA Standards went into effect (1/26/93)? [404.2.5, 303.2] Note: The first ¼ inch of the ½ or ¾ inch threshold may be vertical; the rest must be beveled.	Yes No Measurement: Yes No Measurement: Yes No Measurement:	1/4"max + [Photo #:	Remove or replace threshold

2.43	Is the door equipped with hardware that is operable with one hand and does not require tight grasping, pinching or twisting of the wrist? Door handle? Lock (if provided)? [404.2.7]	Yes No Yes No		MIDDLE PIC Photo #:	Replace inaccessible knob with lever, loop or push hardware Add automatic door opener
2.44	Are the operable parts of the hardware no less than 34 inches and no greater than 48 inches above the floor? [404.2.7]	Yes No Measurement: 42"	34"-48"	Photo #:	Change hardware height
2.45	Can the door be opened easily (5 pounds maximum force)? [404.2.9] Note: You can use a pressure gauge or fish scale to measure force. If you do not have one you will need to judge whether the door is easy to open.	Yes No Measurement: .5	5 lbf	Photo #:	 Adjust or replace closers Install lighter doors Install power-assisted or automatic door openers
2.46	If the door has a closer, does it take at least 5 seconds to close from an open position of 90 degrees to a position of 12 degrees from the latch? [404.2.8.1]	Yes No Measurement:	90° 12°	NO CLOSER Photo #:	• Adjust closer •

Roon	ooms and Spaces – stores, supermarkets, libraries, etc.					
2.47	Are aisles and pathways to goods and services, and to one of each type of sales and service counters, at least 36 inches wide? [403.5.1]	Yes No Measurement: 72"	36" min	Photo #:	 Rearrange goods, equipment and furniture • 	
2.48	Are floor surfaces stable, firm and slip resistant? [302.1]	Yes No		Photo #:	Change floor surface	
2.49	If there is carpet:			111010111	Replace carpet	
2.43	Is it no higher than ½ inch? Is it securely attached along the edges? [302.2]	Yes No Measurement: Yes No	½"max	Photo #:	• Neplace curpet	
Conti		and intercom sys	tems, emergency/alarm boxes, e			
2.50	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward or parallel approach? [305.3]	Yes No Measurement:	48"max		Change height of control	
	Are the operable parts no higher than 48 inches above the floor?* [309.3, 308]	YesNo Measurement:	30"min 48"min		3/15/2012 and a parallel approach is provided, controls can be 54 inches above the floor	

			48"m	48"max	Photo #:	
2.51	Can the control be operated with one hand and without tight grasping, pinching, or twisting of the wrist? [309.4]	Yes No				• Replace control •
					Photo #:	
Seati	ng: Assembly Areas – theater	rs, auditoriums, s	tadiums, thea	iter style classroom	ns, etc.	
2.52	Are an adequate number of	Yes No	# of Seats	Wheelchair Spaces	NA	Reconfigure to add
	wheelchair spaces provided? [221.2.1]	Total #:	4 - 25	1		wheelchair spaces
			26 - 50	2		•
		Wheelchair #:	51 - 150	4		
			151 - 300 300+ soo 201	5 0 Standards 221.2.1.		
			300+ 366 201	0 Stariuarus 221.2.1.	Photo #:	
2.53	Are wheelchair spaces dispersed to allow location choices and viewing angles equivalent to other seating, including specialty seating areas that provide distinct services and amenities? [221.2.3]	Yes No			NA Photo #:	 Reconfigure to disperse wheelchair spaces •

2.54	Where people are expected to remain seated, do people in wheelchair spaces have a clear line of sight over and between the heads of others in front of them? [802.2.1.1, 802.1.1.2]	Yes No	50	NA Photo #:	Alter for line of sight
2.55	Where people are expected to stand, do people in wheelchair spaces have a clear line of sight over and between the heads of others in front of them? [802.2.2.1, 802.1.2.2]	Yes No		NA Photo #:	Alter for line of sight
2.56	If there is a single wheelchair space, is it at least 36 inches wide? [802.1.2]	Yes No Measurement:		NA Photo #:	• Alter space •
2.57	If there are two adjacent wheelchair spaces, are they each at least 33 inches wide? [802.1.2]	Yes No Measurement:	→ 33"min → 33"min →	NA Photo #:	• Alter spaces •

2.58	If the wheelchair space can be entered from the front or rear, is it at least 48 inches deep? [802.1.3]	Yes No Measurement:	48"min	NA Photo#:	• Alter space •
2.59	If the wheelchair space can only be entered from the side, is it at least 60 inches deep? [802.1.3]	Yes No Measurement:	60″min → 600″min → 600″mi	NA Photo #:	• Alter space •
2.60	Do wheelchair spaces adjoin, but not overlap, accessible routes? [802.1.4]	Yes No	Accessibe Route	NA Photo #:	• Alter spaces •
2.61	Is there at least one companion seat for each wheelchair space? [221.3]	Yes No		NA Photo #:	Add companion seats

2.62	Is the companion seat located so the companion is shoulder-to-shoulder with the person in a wheelchair? [802.3.1]	Yes No		NA Photo #:	Alter seating
2.63	Is the companion seat equivalent in size, quality, comfort and amenities to seating in the immediate area? [802.3.2]	Yes No		NA Photo #:	Add equivalent seating
Seati	ng: At dining surfaces (restau	rants, cafeterias,	, bars, etc.) and non-employee w	ork surfaces (libraries, confe	erence rooms, etc.)
2.64	Are at least 5%, but no fewer than one, of seating and standing spaces accessible for people who use wheelchairs? [226.1]	Yes No Total #: Wheelchair #:		NA Photo #:	Alter to provide accessible spaces
2.65	Is there a route at least 36 inches wide to accessible seating? [403.5.1]	Yes No Measurement:	36"min	NA Photo#:	• Widen route •

2.66	At the accessible space(s), is the top of the accessible surface no less than 28 inches and no greater than 34 inches above the floor? [902.3] Note: If for children, the top should be no less than 26 inches and no greater than 30 inches above the floor.	Yes No Measurement:	28"-34"	NA Photo #:	 Alter surface height •
2.67	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward approach? [305.3] Does it extend no less than 17 inches and no greater than 25 inches under the surface? Is there knee space at least 27 inches high and at least 30 inches wide? [306.2, 306.3] Note: If for children, the knee space may be 24 inches high.	Yes No Measurement: Yes No Measurement: Yes No Measurement: Measurement:	27"min 30"min 17"- 25"	NA Photo #: NA	Alter table or work surface Add accessible table or work surface

Seating: General – reception areas, waiting rooms, etc.

2.68	Is there at least one space at least 36 inches wide by at least 48 inches long for a person in a wheelchair? [802.1.2, 802.1.3]	Yes No Measurement:	36"x48"	Photo #:	 Move furniture and equipment to provide space •
Bencl	hes – In locker rooms, dressin	g rooms, fitting r	TOOMS This section does not apply to any		
2.69	In locker rooms, dressing rooms and fitting rooms, is there at least one room with a bench? [222.1, 803.4]	Yes No		NA Photo #:	• Add bench •
2.70	Is there a clear floor space at least 30 inches wide by at least 48 inches long at the end of the bench and parallel to the short axis of the bench? Is the bench seat at least 42 inches long and no less than 20 inches and no greater than 24 inches deep? Does the bench have back support or is it affixed to a wall?	Yes No Measurement: Yes No Measurement: Yes No	48" min 30" min	NA	Move bench Replace bench Affix bench to wall
	Is the top of the bench seat no less than 17 inches and no greater than 19 inches above the floor? [903]	Yes No Measurement:	20"- 24" min		

			17"- 19"	Photo #:	
Checl	k-Out Aisles – supermarkets, l	arge retail stores	s, etc.		
2.71	Is the aisle at least 36 inches wide? [904.3.1]	Yes No Measurement:	36"min	NA Photo #:	Widen aisle
2.72	Is the counter surface of at least one aisle no higher than 38 inches above the floor? [904.3.2]	Yes No Measurement:	38"max	NA Photo #:	• Lower counter •
2.73	Is the top of the counter edge protection no higher than 2 inches above the counter surface? [904.3.2]	Yes No Measurement:	‡ 2"max	NA Photo #:	Lower edge protection

2.74	If there is a check writing surface, is the top no less than 28 inches and no greater than 34 inches above the floor? [904.3.3]	Yes No Measurement:	28"-34"	NA Photo #:	Alter check writing surface•
2.75	If there is more than one check- out aisle is there a sign with the International Symbol of Accessibility at the accessible aisle? [216.11]	Yes No	E	NA Photo #:	• Add sign •
Sales	& Service Counters – banks, s	stores, dry cleane	ers, auto repair shops, fitness clul	bs, etc.	
2.76	Is there a portion of at least one of each type of counter that is: No higher than 36 inches above the floor? At least 36 inches long? [904.4.1]	Yes No Measurement: Yes No Measurement:	36"min 36"max	Photo #:	Lower section of counter Lengthen section of counter
2.77	Does the accessible portion of the counter extend the same depth as the counter top? [904.4]	Yes No Measurement:		Photo #:	Alter accessible portion

2.78	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward or parallel approach? [904.4]	Parallel Measurement: Forward Measurement:	30"min Or 48"min 30"min 48"min	Photo #:	Reconfigure to provide a parallel or forward approach
2.79	For a parallel approach, is the clear floor space positioned with the 48 inches adjacent to the accessible length of counter? [904.4.1]	Yes No Measurement:	48"min	Photo #:	If a parallel approach is not possible, a forward approach is required
2.80	For a forward approach: Do no less than 17 and no greater than 25 inches of the clear floor space extend under the accessible length of the counter? [306.2.2, 306.2.3]	Yes No Measurement:	17-25" 48"min		Reconfigure to provide knee clearance
	Is there at least 27 inches	Yes No			

	clearance from the floor to the bottom of the counter? [306.3.1]	Measurement:	27"min	Photo #:	
Food	- Service Lines – in cafeterias, s	· salad bars, eat-in	fast food establishments, etc.		
2.81	Does at least one of each type of self-service shelf or dispensing device for tableware, dishware, condiments, food and beverages have a forward or parallel approach? [904.5.1]	Yes No Forward Parallel	Or	NA Photo #:	 Reconfigure to provide approach •
				Photo #:	

2.82	If there is an unobstructed parallel approach, is the shelf or dispensing device no higher than 48 inches above the floor? [308.3.1]	Yes No Measurement:	48" max	NA Photo #:	Lower shelf and/or dispensing device
2.83	If there is a shallow obstruction no deeper than 10 inches with a parallel approach, is the shelf or dispensing device no higher than 48 inches above the floor? [308.3.1]	Yes No Measurement:	10" max 48" max	NA Photo #:	Lower shelf and/or dispensing device
2.84	If there is an obstruction no less than 10 inches and no greater than 24 inches deep with a parallel approach, is the shelf or dispensing device no higher than 46 inches above the floor? [308.3.2]	Yes No Measurement:	46" max	NA Photo #:	Lower shelf and/or dispensing device
2.85	If there is an unobstructed forward approach, is the shelf or dispensing device no higher than 48 inches above the floor? [308.2.1]	Yes No Measurement:	48"max	NA Photo #:	Lower shelf and/or dispensing device


2.86	If there is an obstruction no deeper than 20 inches with a forward approach: Does clear floor space extend under the obstruction that is at least the same depth as the obstruction? Is the shelf or dispensing device no higher than 48 inches above the floor? [904.5.1]	Yes No Measurement: Yes No Measurement:	20"max 20"min	NA Photo #:	Reconfigure to provide knee space Lower shelf and/or dispensing device
2.87	If the obstruction is no less than 20 inches and no greater than 25 inches deep with a forward approach: Does clear floor space extend under the obstruction that is at least the same depth as the obstruction? Is the shelf or dispensing device no higher than 44 inches above the floor? [904.5.1]	Yes No Measurement: Yes No Measurement:	20"-25" 44" max	NA Photo #:	Reconfigure to provide knee space Lower shelf and/or dispensing device
2.88	If there is a tray slide, is the top no less than 28 inches and no greater than 34 inches above the floor? [904.5.2]	Yes No Measurement:	28"-34"	NA Photo #:	• Reconfigure •

Yes No		•
		•
	Photo #:	
Yes No		•
		•
	Photo #:	
Yes No		•
		•
	Photo #:	
Yes No		•
		•
	Photo #:	
Yes No		•
		•
	Photo #:	

The ADA Checklist for Existing Facilities

Priority 3 - Toilet Rooms

Based on the 2010 ADA Standards for Accessible Design



Project

Building WEST ANNEX

Location CORONER'S SIDE OF BUILDING

Date 10/11/2021

Surveyors LARRY WEAVER

SHERI GAILLARD

Contact Information

574-242-2508

When toilet rooms are open to the public they should be accessible to people with disabilities.



Institute for Human Centered Design www.HumanCenteredDesign.org 2014



ADA National Network
Questions on the ADA 800-949-4232 voice/tty
www.ADAchecklist.org

This checklist was produced by the New England ADA Center, a project of the Institute for Human Centered Design and a member of the ADA National Network. This checklist was developed under a grant from the Department of Education, NIDRR grant number H133A060092-09A. However the contents do not necessarily represent the policy of the Department of Education, and you should not assume endorsement by the Federal Government.

Questions or comments on the checklist contact the New England ADA Center at 617-695-0085 voice/tty or ADAinfo@NewEnglandADA.org

For the full set of checklists, including the checklists for recreation facilities visit www.ADAchecklist.org.

Copyright © 2016 ADA Checklist for Existing Materials. You can freely reproduce and distribute this content. Include proper attribution. But you must get permission before using this content as a fee-based product.

Prio	rity 3 – Toilet Rooms			Comments	Possible Solutions
3.1	If toilet rooms are available to the public, is at least one toilet room accessible? (Either one for each sex, or one unisex.) Note: If toilet rooms are chiefly for children, e.g., in elementary schools and day care centers, use the children's specifications in Toilets - 604.1, 604.8, 604.9, 609.4 and Lavatories and Sinks – 606.2.	Yes No		Photo #:	 Reconfigure toilet rooms Combine toilet rooms to create one unisex accessible toilet room
3.2	Are there signs at inaccessible toilet rooms that give directions to accessible toilet rooms? [See 2010 ADA Standards for Accessible Design – 216.8]	Yes No	AND STATE OF THE PARTY OF THE P	Photo #:	Install signs•
3.3	If not all toilet rooms are accessible, is there a sign at the accessible toilet room with the International Symbol of Accessibility? [216.8]	Yes No	Ġ	Photo #:	Install sign
Acce	ssible Route				
3.4	Is there an accessible route to the accessible toilet room? [206.2.4]	⊠Yes			Alter route
				Photo #:	

Signs at Toilet Rooms 3.5 Do text characters contrast with Yes SIGN IS ON DOOR/NEEDS • Install tactile sign their backgrounds? **MOVED** Relocate sign [703.5] Yes Are text characters raised? [703.2] Yes No Is there Braille? [703.3] MEN Is the sign mounted: Yes No On the wall on the latch side of the door? [703.4.2] Note: Signs are permitted on the push side of doors with closers and without hold-open devices. Yes No With clear floor space beyond centered on the arc of the door swing *If constructed before tactile characters between the closed position Measurement: 3/15/2012 and a person and 45-degree open position, at may approach within 3 inches of the sign without least 18 x 18 inches centered on the tactile characters? * encountering protruding 18, min objects or standing within [703.4.2] the door swing, relocation not required No So the baseline of the lowest *If constructed before character is at least 48 inches 3/15/2012 and mounted 60"max above the floor and the no higher than 60 inches Measurement: 48"min baseline of the highest to the centerline of the character is no more than 60 sign, relocation is not

	inches above the floor? * [703.4.1]				required
	Note: If the sign is at double doors with one active leaf, the sign should be on the inactive leaf; if both leaves are active, the sign should be on the wall to the right of the right leaf.			Photo #:	
Entra	nce				
3.6	Is the door opening width at least 32 inches clear, between the face of the door and the stop, when the door is open 90 degrees? [404.2.3]	Yes No Measurement: 39"	32"min 90°		 Install offset hinges Alter the doorway
				Photo #:	
3.7	If there is a front approach to the pull side of the door is there at least 18 inches of maneuvering clearance beyond the latch side plus 60 inches clear depth? Note: See 2010 Standards 404.2.4 for maneuvering clearance requirements on the push side of the door and side approaches to the pull side of the door	Yes No Measurement: 50X81	60" min		 Remove obstructions Reconfigure walls Add automatic door opener
	On both sides of the door, is the				

	floor surface of the maneuvering clearance level (no steeper than 1:48)? [404.2.4]	Yes No Measurement:		Photo #:	
3.8	If the threshold is vertical is it no more than ¼ inch high? Or No more than ½ inch high with the top ¼ inch beveled no steeper than 1:2, if the threshold was installed on or after the 1991 ADA Standards went into effect (1/26/93)? Or No more than ¾ inch high with the top ½ inch beveled no steeper than 1:2, if the threshold was installed before the 1991 ADA Standards went into effect (1/26/93)? [404.2.5, 303.2] Note: The first ¼ inch of the ½ or ¾ inch threshold may be vertical; the rest must be	Yes No Measurement: Yes No Measurement: Yes No Measurement:	1/4"max + [FLAT SURFACE	Remove or replace threshold
	beveled.		3/4"max -	Photo #:	

3.9	Is the door equipped with hardware that is operable with one hand and does not require tight grasping, pinching or twisting of the wrist? Door handle? Lock (if provided)? [404.2.7]	Yes No		MIDDLE PICTURE	Replace inaccessible knob with lever, loop or push hardware Add automatic door opener
	ri			Photo #:	
3.10	Are the operable parts of the door hardware mounted no less than 34 inches and no greater than 48 inches above the floor? [404.2.7]	Yes No Measurement: 34.5"	34"-48"	Photo #:	Change hardware height
3.11	Can the door be opened easily (5 pounds maximum force)? [404.2.9] Note: You can use a pressure gauge or fish scale to measure force. If you do not have one you will need to judge whether the door is easy to open.	Yes No Measurement: 1	5 lbf	Photo #:	Adjust or replace closers Install lighter doors Install power-assisted or automatic door openers


3.12	If the door has a closer, does it take at least 5 seconds to close from an open position of 90 degrees to a position of 12 degrees from the latch? [404.2.8.1]	Yes No Measurement:	90° 12°	NO CLOSER Photo #:	Adjust closer•
3.13	If there are two doors in a series, e.g. vestibule, is the distance between the doors at least 48 inches plus the width of the doors when swinging into the space? [404.2.6]	Yes No Measurement:	48"min — or 48"min —	NA	Remove inner door Change door swing
				Photo #:	

3.14	If there is a privacy wall and the door swings out, is there at least 24 inches of maneuvering clearance beyond the door latch side and 42 inches to the privacy wall? [404.2.4]	Yes No Measurement:	24"min 48"min privacy wall	NA Photo #:	Reconfigure space•
3.15	If there is a privacy wall and the door swings in, is there at least 24 inches of maneuvering clearance beyond the door latch side and at least 48 inches to the privacy wall if there is no door closer or at least 54 inches if there is a door closer? [404.2.4]	Yes No Measurement:	48"min privacy wall	NA Photo #:	 Reconfigure space •
In the	Toilet Room				
3.16	Is there a clear path to at least one of each type of fixture, e.g. lavatory, hand dryer, etc., that is at least 36 inches wide? [403.5.1]	Yes No Measurement: 78"	36"min		 Remove obstructions •
				Photo #:	
3.17	Is there clear floor space available for a person in a wheelchair to turn around, i.e. a circle at least 60 inches in diameter or a T-shaped space within a 60-inch square? [603.2.1]	Yes No Measurement:	36"	Photo #:	 Move or remove partitions, fixtures or objects such as trash cans •

3.18	In a single user toilet room if the door swings in and over a clear floor space at an accessible fixture, is there a clear floor space at least 30 x 48 inches beyond the swing of the door? [603.2.3 Exception 2]	Yes No Measurement:	A STATE OF THE STA	DOOR SWINGS OUTWARD Photo #:	 Reverse door swing Alter toilet room
3.19	If the mirror is over a lavatory or countertop, is the bottom edge of the reflecting surface no higher than 40 inches above the floor? Or If the mirror is not over the lavatory or countertop, is the bottom edge of the reflecting surface no higher than 35 inches above the floor?* [603.3]	Yes No Measurement: 40" Yes No Measurement:	40" max	Photo #:	* If installed before 3/15/2012 and the bottom edge of the reflecting surface is no higher than 40 inches above the floor, lowering the mirror to 35 inches is not required • Lower the mirror • Add another mirror
3.20	If there is a coat hook, is it no less than 15 inches and no greater than 48 inches above the floor?* [603.4]	Yes No Measurement: 62"	48"max 15"min	Photo #:	Adjust hook Replace with or provide additional accessible hook If installed before 3/15/2010 and the clear floor space allows a parallel approach, the coat hook may be 54 inches above the floor.

3.21	Does at least one lavatory have				Alter lavatory
3.21	a clear floor space for a forward approach at least 30 inches wide and 48 inches long? [606.2]	Yes No Measurement:	48"min 30"min	Photo #:	Replace lavatory
				riioto #.	
3.22	Do no less than 17 inches and no greater than 25 inches of the clear floor space extend under the lavatory so that a person using a wheelchair can get close enough to reach the faucet? [306.2] Is the front of the lavatory or counter surface, whichever is higher, no more than 34 inches above the floor? [606.3]	Yes No Measurement: 17" Yes No Measurement: 30"	48" 34"max	Photo #:	 Alter lavatory Replace lavatory Alter lavatory Replace lavatory
				Photo #:	
3.24	Is there at least 27 inches clearance from the floor to the bottom of the lavatory that extends at least 8 inches under the lavatory for knee clearance? [306.3.3]	Yes No Measurement: 9"	*8"≯ min 27"min		Alter lavatory Replace lavatory
	[555.5.5]			Photo #:	

3.25	Is there toe clearance at least 9 inches high? [306.3.3] Note: Space extending greater than 6 inches beyond the available toe clearance at 9 inches above the floor is not considered toe clearance.	Yes No Measurement: 12"	g"" —6"+ min" max 48"	Photo #:	Alter lavatoryReplace lavatory
3.26	Are pipes below the lavatory insulated or otherwise configured to protect against contact? [606.5]	Yes No		Photo #:	 Install insulation Install cover panel
3.27	Can the faucet be operated without tight grasping, pinching, or twisting of the wrist? Is the force required to activate the faucet no greater than 5 pounds? [606.4]	Yes No		Photo #:	Adjust faucet Replace faucet



	floor?				
	Above lavatories less than 20 inches deep: no higher than 48 inches above the floor?	Yes No Measurement:	48"max		
	Not over an obstruction: no higher than 48 inches above the floor? [308.2]	Yes No Measurement:			
	Can the operable parts of the hand dryer or towel dispenser be operated without tight grasping, pinching or twisting of the wrist?	Yes No	48"max		
	Is the force required to activate the hand dryer or towel dispenser no greater than 5 pounds?	Yes No Measurement:			
	[309.4]			Photo #:	
Wate	r Closets in Single-User Toilet	Rooms and Com	partments (Stalls) The 2010 Standar	rds refer to toilets as water closets.	
3.30	Is the centerline of the water closet no less than 16 inches and no greater than 18 inches	Yes No Measurement:			 Move toilet Replace toilet Move partition
	from the side wall or partition? [604.2]	17"	16"-18"		•
			Į	Photo #:	

3.31	Is clearance provided around the water closet measuring at least 60 inches from the side wall and at least 56 inches from the rear wall?* [604.3.1]	Yes No Measurement: 42X65	56"min	WILL NEED TO REMOVE URINAL	* If constructed before 3/15/12, clearances around water closets in single user toilet rooms can be 48 inches wide by 66 inches long or 48 inches wide by 56 inches long (depending on the approach to the water closet, see 1991 Standards Figure 28) and the lavatory may overlap that clearance if the door to the room does not swing into the required clearances at fixtures (such as lavatories, water closet and urinals) and the edge of the lavatory is at least 18 inches from the centerline of the water closet • Alter room/compartment for clearance
				r noto #.	

3.32	Is the height of the water closet no less than 17 inches and no greater than 19 inches above the floor measured to the top of the seat? [604.4]	Yes No Measurement: 15.5"	17"-19"	Photo #:	 Adjust toilet height Replace toilet
3.33	Is there a grab bar at least 42 inches long on the side wall?	Yes No Measurement: 24"	54"min ————————————————————————————————————		Install grab barRelocate grab barRelocate objects
	Is it located no more than 12 inches from the rear wall?	Yes No Measurement: 17"			
	Does it extend at least 54 inches from the rear wall? [604.5.1]	Yes No Measurement: 41"			
	Is it mounted no less than 33 inches and no greater than 36 inches above the floor to the top of the gripping surface? [609.4]	Yes No Measurement: 31"	33"-36"		* If constructed before 3/15/2012 grab bars do
	Is there at least 12 inches clearance between the grab bar and projecting objects above?*	Yes No Measurement: NOTHING	12"min		not need to be relocated; there are no space requirements above and below grab bars in the
	Is there at least 1½ inches clearance between the grab bar and projecting objects below?*	ABOVE Yes No Measurement: NOTHING	1½"min.‡		1991 Standards

	Is the space between the wall and the grab bar 1 ½ inches? [609.3]	BELOW Yes No Measurement:		Photo #:	
3.34	Is there a grab bar at least 36 inches long on the rear wall? Does it extend at least 12 inches from the centerline of the water closet on one side (side wall)? Does it extend at least 24 inches on the other (open) side? [604.5.2] Is it mounted no less than 33 inches and no greater than 36 inches above the floor to the top of the gripping surface? [609.4] Are there at least 12 inches clearance between the grab bar and protruding objects above?*	Yes No Measurement: Yes No Measurement: Yes No Measurement: Yes No Measurement: Yes No Measurement:	36"min 12" 24"min — min 12" 33"-36"	NO BAR	 Install grab bar Relocate grab bar Relocate objects
	Are there at least 1½ inches clearance between the grab bar and projecting objects below?*	Yes No Measurement:	1½"min \$		* If constructed before 3/15/2012 grab bars do not need to be relocated;

	Is the space between the wall and the grab bar 1½ inches? [609.3]	Yes No Measurement:		Photo #:	there are no space requirements above and below grab bars in the 1991 Standards
3.35	If the flush control is hand operated, is the operable part located no higher than 48 inches above the floor? [604.6]	Yes No Measurement:	48"max	Photo #:	Move control Install sensor with override button no higher than 48 inches
3.36	If the flush control is hand operated, can it be operated with one hand and without tight grasping, pinching, or twisting of the wrist? Is the force required to activate the flush control no greater than 5 pounds?	Yes No Yes No Measurement:			Change control Adjust control
3.37	[605.4] Is the flush control on the open side of the water closet? [604.6]	Yes No	→ open side →	Photo #: Photo #:	Move control

3.38	Is the toilet paper dispenser located no less than 7 inches and no greater than 9 inches from the front of the water closet to the centerline of the dispenser?* [604.7]	Yes No Measurement: NO TOILET PAPER DISPENSER	7-9"	Photo #:	* If constructed before 3/15/2012 dispenser does not need to be relocated if it is within reach from the water closet seat; the 1991 Standards do not specify distance from the front of the water closet • Relocate dispenser •
3.39	Is the outlet of the dispenser: Located no less than 15 inches and no greater than 48 inches above the floor? Not located behind grab bars? [604.7]	Yes No Measurement: Yes No	outlet 48" max outlet 15" min	Photo #:	Relocate dispenser
3.40	Does the dispenser allow continuous paper flow? [604.7]	Yes No		Photo #:	 Adjust dispenser Replace dispenser

3.41	Is the door opening width at least 32 inches clear, between the face of the door and the stop, when the door is open 90 degrees? [604.8.1.2]	Yes No Measurement:	32"min	NA Photo #:	Widen door width
3.42	If there is a front approach to the pull side of the door, is there at least 18 inches of maneuvering clearance beyond the latch side plus 60 inches clear depth? [604.8.1.2] Note: See 2010 Standards 604.8.1.2 Doors for maneuvering clearance requirements on the push side of the door and side approaches to the pull side of the door	Yes No Measurement:	18"min 60"min	NA Photo #:	• Remove obstructions •
3.43	Is the door self-closing? [604.8.1.2]	Yes No		NA Photo #:	Add closer Replace door

3.44	Are there door pulls on both sides of the door that are operable with one hand and do not require tight grasping pinching or twisting of the wrist?* [604.8.1.2]	Yes No		NA Photo #:	* If constructed before 3/15/2012 door pulls do not need to be added; door pulls are not required in the 1991 Standards • Replace hardware •
3.45	Is the lock operable with one hand and without tight grasping, pinching or twisting of the wrist? [309.4]	Yes No		NA Photo #:	• Replace lock •
3.46	Are the operable parts of the door hardware mounted no less than 34 inches and no greater than 48 inches above the floor? [404.2.7]	Yes No Measurement:	34"-48"	NA Photo #:	Relocate hardware
3.47	Is the compartment at least 60 inches wide? [604.8.1.1]	Yes No Measurement:	60"min	NA Photo #:	Widen compartment


3.48	If the water closet is wall hung, is the compartment at least 56 inches deep? [604.8.1.1]	Yes No Measurement:	56"min →	NA	Widen compartment
3.49	If the water closet is floor mounted, is the compartment at least 59 inches deep? [604.8.1.1]	Yes No Measurement:	59"min —	Photo #: NA Photo #:	Alter compartment
3.50	If the door swings in, is the minimum required compartment area provided beyond the swing of the door (60 inches x 56 inches if water closet is wall hung or 59 inches if water closet is floor mounted)? [604.8.1.1]	Yes No Measurement:	60"min	NA Photo #:	 Reverse door swing Alter compartment
		Yes No		Photo #:	•
		Yes No		Prioto #:	•

ADA Checklist for Existing Facilities		Prio	rity 3 – Toilet Rooms
		Photo #:	
	Yes No		•
			•
		Photo #:	

ADA Checklist for Existing Facilities

Priority 4 – Additional Access

Based on the 2010 ADA Standards for Accessible Design



Project	
Building WEST ANNEX	
Location 108 N FRANKLIN ST	
Date 10/11/2021	
Surveyors LARRY WEAVER	
SHERI GAILLARD	
Contact Information	
574-242-2508	

Amenities such as drinking fountains and public telephones should be accessible to people with disabilities.





This checklist was produced by the New England ADA Center, a project of the Institute for Human Centered Design and a member of the ADA National Network. This checklist was developed under a grant from the Department of Education, NIDRR grant number H133A060092-09A. However the contents do not necessarily represent the policy of the Department of Education, and you should not assume endorsement by the Federal Government.

Questions or comments on the checklist contact the New England ADA Center at 617-695-0085 voice/tty or ADAinfo@NewEnglandADA.org

For the full set of checklists, including the checklists for recreation facilities visit www.ADAchecklist.org.

Copyright © 2016 ADA Checklist for Existing Materials. You can freely reproduce and distribute this content. Include proper attribution. But you must get permission before using this content as a fee-based product.

Prio	rity 4 – Additional Access			Comments	Possible Solutions	
Drinl	Drinking Fountains					
4.1	Does at least one drinking fountain have a clear floor space at least 30 inches wide x at least 48 inches long centered in front of it for a forward approach?* [See 2010 ADA Standards for Accessible Design – 602.2]	Yes No Measurement:	48"min 30"min	NA Photo #:	*If installed before 3/15/2012, a parallel approach is permitted and the clear floor space is not required to be centered • Alter space • Relocate drinking fountain • Install a drinking fountain in another location	
4.2	If there is a forward approach, do no less than 17 inches and no greater than 25 inches of the clear floor space extend under the drinking fountain? [306.2.2, 306.2.3] Note: If the drinking fountain is primarily for children's use and the spout is no more than 30 inches above the floor and no more than 3½ inches from the edge of the unit, a parallel approach is permitted.	Yes No Measurement:	17".25"	NA Photo #:	 Alter space Replace drinking fountain 	

4.3	If the drinking fountain is no deeper than 20 inches, are the operable parts no higher than 48 inches above the floor? [308.2.2]	Yes No Measurement:	20" max 48" max	NA Photo #:	 Adjust drinking fountain Replace drinking fountain
4.4	If the drinking fountain is no less than 20 inches and no greater than 25 inches deep, are the operable parts no higher than 44 inches above the floor? [308.2.2]	Yes No Measurement:	20"min to 25"max 44" max	NA Photo #:	 Adjust drinking fountain Replace drinking fountain
4.5	Can the control be operated with one hand and without tight grasping, pinching or twisting of the wrist? Is the force required to activate the control no more than 5 pounds? [309.4]	Yes No Yes No Measurement:	and the state of t	NA Photo #:	 Change control Adjust control
4.6	Is the spout outlet no higher than 36 inches above the floor? [602.4]	Yes No Measurement:	36" max	NA Photo #:	Adjust drinking fountain Replace drinking fountain

4.7	Is the spout: At least 15 inches from the rear of the drinking fountain? No more than 5 inches from the front of the drinking fountain? [602.5]	Yes No Measurement: Yes No Measurement:	o o o o o o o o o o o o o o o o o o o	NA	Adjust spout Replace drinking fountain
4.8	If there is more than one drinking fountain, is there at least one for standing persons? [211.2] Is the spout outlet no lower than 38 inches and no higher than 43 inches above the floor? [602.7]	Yes No Yes No Measurement:	38" to 43"	Photo #: NA Photo #:	Adjust drinking fountain Install new drinking fountain for standing height
4.9	If the leading (bottom) edge of the fountain is higher than 27 inches above the floor, does the front of the fountain protrude no more than 4 inches into the circulation path? [307.2]	Yes No Measurement:	27"	NA Photo #:	 Adjust drinking fountain Replace drinking fountain Add tactile warning such as permanent planter or partial walls

Public Telephones						
4.10	Does at least one telephone have a clear floor space at least 30 inches wide x at least 48 inches long for a parallel or forward approach? [704.2.1]	Yes No	48"min 30"min	NA	 Move telephone Install new telephone for clear floor space 	
			30"min	Photo #:		
4.11	Is the highest operable part of the telephone no higher than 48 inches above the floor? [704.2.2]	Yes No Measurement:	48" max	NA Photo #:	Adjust telephone Output	
4.12	If the leading (bottom) edge of the telephone is higher than 27 inches above the floor, does the front of the telephone protrude no more than 4 inches into the circulation path? [307.2]	Yes No Measurement:	> 27"	NA Photo #:	Adjust telephone	

4.13	Does at least one telephone have a volume control? [704.3]	Yes No	PRESS TO CHANGE VOLUME 3 LEVELS	NA Photo #:	Install volume control Replace telephone with one that has volume control
4.14	Is the volume control identified by a pictogram of a telephone handset with radiating sound waves? [703.7.2.3]	Yes No		NA Photo #:	Add pictogram
4.15	Does at least one telephone have a TTY? [217.4.1] Note: TTY's are devices that employ interactive text-based communication through the transmission of coded signals across the telephone network. They are mainly used by people who are deaf and/or cannot speak.	Yes No		NA Photo #:	• Install TTY •

4.16	Is the touch surface of the TTY keypad at least 34 inches above the floor? [704.4.1] Note: If a seat is provided, the TTY is not required to be 34 inches minimum above the floor.	Yes No Measurement:	34"min	NA Photo #:	Adjust height of TTY
4.17	Is the TTY identified by the International Symbol of TTY? [703.7.2.2]	Yes No		NA Photo #:	• Add symbol •
4.18	Do signs that provide direction to public telephones also provide direction to the TTY? [216.9.2]	Yes No	Phone	NA Photo #:	• Add signs •
4.19	Do telephones that do not have a TTY provide direction to the TTY? [216.9.2]	Yes No		NA Photo #:	• Add signs •

Fire Alarm Systems						
4.20	If there are fire alarm systems, do they have both flashing lights and audible signals? [702.1]	Yes No	F I F I R E	NO ALARM SYSTEM OR SMOKE ALARMS Photo #:	 Install audible and visual alarms • 	
				Prioto #.		
		Yes No			•	
					•	
				Photo #:		
		Yes No			•	
		iesino			•	
					•	
				Photo #:		
		Yes No			•	
					•	
				Photo #:		
		Yes No			•	
					•	
					•	
				Photo #:		